

























Event Equipment

TABLE OF CONTENTS







Specialists in portable flooring, we propose our standard dance floor system: TANGO

SIMPLE, QUICK, AND DURABLE





TANGO floors are **versatile** and **scalable**. They have become the reference product; dancers, both amateur and professional, prefer.

System

The simple system consists of panels, edge pieces, anchoring plates, and screws.

The four corners of the floor panels have been drilled. The holes fit over pins on the junction plates, and a screw with a countersunk head holds the panel to the plate.

The edge pieces work in the same way. Thus, a junction plate can connect four panels, two panels and two edge pieces, or one panel, two edge pieces and a corner.



Floor panels



The floor base is made of MDF (Medium Density Fibreboard), dimensions $1 \times 1 m$, thickness 22 mm.

Both sides of the panel are surfaced with a sheet with a floorboard design and a highly resistant protective overlay hot glued to the panel.

The edges of the panels are protected with a PVC edge piece.

DOUBLE SIDED FACING = TWICE THE LIFESPAN!

2 sides standard colouring Beech - Beech



The panels are faced on both sides, and thus are reversible. Our **standard** panel has a beech coloured veneer on both sides. With the **Wenge - Light Maple** panel, you can configure the floor any way you wish: solid colour, checkerboard, lines...



1 side Wenge

1 side Light Maple





Assembly

The various components are assembled using junction plates. These plates are equipped with four resistant hexagonal inserts, threaded on the interior. Screws are used to affix the panels and edge pieces.





Finishing







The edge of the dance floor is trimmed with bevelled, corrugated aluminium edge pieces to facilitate access to the floor.

Storage

Strengthened by its extensive experience in installing portable flooring, we are always optimising storage methods for our products with the goal of simplifying the task for those who work with our floors.

The 25m² KIT is specially designed for hotel-restaurants; 1.80 x 0.80m cart and a flight-case.



Technical specifications

The 50m² KIT is ready to assemble and compact; 1.60 x 1.10m cart and two flight-cases.



Pallet with foldable collars, and cover.



Floor panels	MDF - beech wood design	1 x 1 m x 22 mm
Edge pieces	Aluminium 1 x 0,15	
Junction plates	Galvanised steel	0,20 x 0,20 m
Assembled floor	Total thickness 25mm	-

Resists cigarette burns, stains, scratches, easy to maintain, and resistant to certain products.



An additional advantage...

Use the dance floor panels to make a rostrum! (See pages 7 and 8)





Panels

- For indoor use: 2 x 1m panel, 22mm thickness MDF with wood floor design.

- For outdoor use: 2 x 1m panel, 22mm thickness MDF with 3 ply spruce veneer, may also be used indoors.





Technical specifications

Floor panels	MDF or spruce	2 x 1 m x 22 mm
Edge pieces	Aluminium	2 ó 1 m x 0,15 m
Junction plates	Galvanised steel	0,20 x 0,20 m
Assembled floor	Total thickness 25mm	-

Resists cigarette burns, stains, scratches, easy to maintain, and resistant to certain products.













AUTO-CLIC Floor



Description

AUTO-CLIC is an exclusive portable dance floor system that requires **no tools or screws** for installation. The quality of the system makes it a product that both amateurs and professionals love.



When dancing and installing become a pleasure



Assembly

The assembly is done by interlocking, <u>without tools.</u> The blocking of the floors between them is done by a system of interlocking holes and lugs.



Panels



The Auto-click system is composed of panels 2m x 0,50m and 1m x 0,50m.

The assembly is done in offset type brick wall.

Borders

On the periphery it is possible to fix aluminum ramps to catch up with the height of the floor.



Storage

The Flight case for the borders





Technical specifications

Panels	MDF - wood design / Plywood P.C.	2m ou 1m x 0,5m x 22 mm
Borders	Aluminium	1 x 0,12 m
Assembled floor	Total thickness 32mm	=

Resists cigarette burns, stains, scratches, easy to maintain, and resistant to certain products.





Plywood with a phenolic coating



A simple, practical, and ingenious system, **Estradium** is an evolution of our portable dance floor, transformed into a riser.

Estradium is designed for all types of use:

podiums, fashion shows, showcase, choir risers, orchestra director's podium, flooring for booths...



System

A metallic frame upon which a panel is attached. The screws used for attachment also hold the feet in place.





Several heights: 20cm - 40cm - 60cm 80cm - 100cm (with supports)



The feet are made of 50mm galvanised steel tubes with mounting tips.

All feet have an adjustable caster (20mm of play).

ESTRADIUM (continued)

Advantages

Estradium has many advantages:

Its finish: wood flooring design Its ease of handling: 1 x 1m modules Its modularity: several heights available Its durability: metal frame



Accessories

Stairs

Railings

Stage skirting

Collars









Storage

Carts



The panels can also be stacked on top of each other.



Technical specifications

Floor panels	MDF beech wood design - 1 x 1m - 22mm thickness
Frames	Electrostatically painted steel: hammered black - 1 x 1m - 30 x 30mm tube
Feet	Galvanised steel - Heights 20 - 40 - 60 - 80 - 100cm - 500 Kg/m²



An additional advantage... Floor panels may be used with our Tango dance floor system.

(See pages 3 and 4)



Les Z'empilables

Description

Les **Z'empilables** can be rostrums, choir risers, school lecture hall risers, awards podiums, display shelves...

The clever little modules that stack, build, and change for all your needs!

System

To fit together, the feet attach to the specially designed rounded tubes. Modules can be connected together with a screw and a wing nut. The bottoms of the feet have plastic casters to protect the floor.

A railing may be installed on the back and sides for safety.





There are many possible configurations, with one, two, three levels or more...









Technical specifications

Frames	1.06 x 0.50m - 0.22m tall - steel with decorative black painted finish
Floor panels	1 x 0.50m - 2mm thickness - MDF beech wood design

ESTRADE CHORALE





Estrade Chorale is simple, practical, and scalable!

Composed of 1 x 0.50m frames with feet of 20cm 40cm and 60cm tall, beech wood finished MDF panels and safety railings.

The ideal product for: Choirs, group photos...







System

Frames of the same height are assembled with screws, and the risers are connected together with collars. The feet screw into the frames and the screw heads attach the panels, which are pre-drilled on the bottom.









There are many possible configurations:





Technical specifications

Floor panels	MDF beech wood design - 1 x 0.50m - 22mm thickness
Frames	Electrostatically painted steel: hammered black finish - 1 x 0.50m - 30 x 30mm tube
Feet	Galvanised steel - Heights 20 - 40 - 60 - 80 - 100cm - 500 Kg/m²

TRIBUNE V.I.P



Description

The tribune V.I.P. is ideal for ceremonies, plays, sports events... Constructed of 1 x 1m frames with feet of 20cm, 40cm, and 60cm tall, wood finished MDF panels, and safety railings.

Frames of the same height are assembled with screws, and the risers are connected together with collars.







On each level, there is a safety bar.



There are many possible configurations:



In straight rows

Technical specifications

Floor panels	MDF beech wood design - 1 x 0.50m - 22mm thickness
Frames	Electrostatically painted steel: hammered black finish - 1 x 0.50m - 30 x 30mm tube
Feet	Galvanised steel - Heights 20 - 40 - 60 - 80 - 100cm - 500 Kg/m²



Polka floor

Description

The **Polka floor** is based on our Tango dance floor system, and can be used both indoors and outdoors.

System

Identical to the Tango system, it is composed of panels, edge pieces, junction plates and screws.



Panels

The Polka floor is an outdoor quality plywood floor.



Storage





The 50m² KIT is ready to assemble and compact; 1.60 x 1.10m cart and two flight-cases.



Pallet with foldable



Technical specifications

Floor panels	Outdoor plywood	1 x 1 m x 22 mm	1,22 x 1,22 m x 22 mm
Edge pieces	Aluminium	1 x 0,15 m	1,22 x 0,15 m
Junction plates	Galvanized steel	0,20 x 0,20 m	0,20 x 0,20 m
Assembled floor	Total thickness 25mm	-	-









The **Country ballroom floor** is specially designed for your outdoor festivities, various events, dances, patios, skating rink supports...





System

The system consists of adjustable feet, lateral pieces, and floor panels. The pins on the lateral pieces fit into the rings on the adjustable feet.

This forms a metal grid upon which the floor panels are laid. The panels are blocked with cleats attached to the bottom of the floor panels.









Storage

The pallet rack with removable posts for stacking the panels



The mesh pallet for storage of the lateral pieces and adjustable feet.



Technical specifications





Floor panels	Exterior quality plywood1,22 x 1,22 m xfinished with a phenolic coating	
Lateral pieces	Galvanized steel	1,17 m
Feet	Galvanized steel	Adjustable from 18.5 to 23.5cm
Options	Galvanized steel	railings
	Aluminium	ramp



An additional advantage...

The floor panels are compatible with our Sceniom system! (see pages 15 and 16)

OUTDOOR FLOORING





Autobloc is a self-blocking flooring system. It has a simple, quick assembly system that requires no tools or screws.

It is designed for creating large areas such as tents, floor protection, skating rinks...





System

The panels are attached using cleats with pins that fit into pre-drilled holes under the panels.

Thus assembled, the panels are blocked and will not move.







"Brick wall" assembly with 2 x 1m and 1 x 1m panels



Floor access is facilitated with borders that attach to the edges.



Technical specifications

Floor panels	21mm 3 ply Fir	2 x 1m and 1 x 1m
Cleats	Autoclave treated Pine	21mm thickness
Borders	3 ply Fir - left and right	0.25 x 1m

OUTDOOR FLOORING





Sceniom is a variable height stage, specially designed for all your indoor or outdoor shows, and events. The hot dip galvanized steel structure is composed of adjustable height feet, trusses and crossbars that form a $2.44 \times 2.44m$ or 1.22mgrid. The outdoor quality plywood floor panels rest on top of the structure and are blocked with cleats.







Stairway



To access the stage, we have refined a 7 step stairway that adapts to any possible height. This stairway is equipped with 2 railings and a safety locking system.

Railing









Sceniom can be equipped with railings composed of posts, bars and screens.

The posts fit onto the feet. They are blocked by our exclusive spring loaded backstop system.

The bars fit into the grommets in the safety screens, and then attach to the pins on the posts, fastened by clips.

The high-strength screens are customizable.

Stage skirting





The stage skirting, in black pre-perforated PVC fabric, can be installed quickly with little straps that wrap around the structure.

Storage

Storage pallets for storing the floor panels



Option

 Cover quick and easy



Technical specifications

Structure	Hot Dip Galvanized steel
Heights	0.90 to 1.40m with fine adjustment by 5cm cylinders
Floor panels	24mm thick plywood - 1.22 x 1.22m size Exterior quality finished with a phenolic coating
Strength	500 Kg/m²



An additional advantage...

The floor panels are compatible with our Country ballroom system! (see page 13)

TRAILER-STAGE TRI024



Description

Trio 24 is a multi-use trailer, the ideal product for all your parties, ceremonies, concerts...







System





The floorboards rest on the prop stands.







Access stair integrated into the trailer.



Rear safety railings

Installing the tent, attached to the trailer by screws.







TRIO24: the solution...



Black PVC stage skirting on the front.

iront.





Technical characteristics

Exterior dimensions	6.12 x 2.32m, 6 x 4m stage
Height from ground to stage	0.75m
Sliding foldab	ne multiply wood floor ole three-step stairway 7 weight: 1,090kg - Class E licence



CADRE EXPO



Description

Cadrexpo is the ideal solution for creating a floor for your booth.

It is a 1 x 1m frame of 30mm square metal tubing equipped with 4 adjustable cylinders.

The frames attach to each other with screws. They can be levelled from the top or the bottom.

The adjustable height is between 7cm (min.) and 9cm (max.) and the floor height is 2.5cm. The floor panels rest on the structure and are blocked either by cleats attached to the bottom, or by edge sheets.





Panels

Technical specifications

Frames	<i>Frames</i> Electrostatically painted steel: hammered black finish 1 x 1 m - Tubo 30 x 30	
Panels	1 x 1m 22mm thickness	
Height	7cm + 2cm of adjustment	



The USF adjustable floor structure can be used for all types of expositions (booths, display shelves...).

Its wide range of uses makes it the product for all your needs.







System

Its structure consists of adjustable feet (from the top) and lateral beams. Linked together, they form a grid upon which the floor panels $(1 \times 1m)$ rest.

Assembles without tools





The floor panels are blocked using cleats attached to the underside.

The free space under the structure allows



wiring, pipes, etc... to be installed easily.

Storage

Pallets with collars



 Flight cases (for storing the structure)



Carts



Technical specifications

Adjustable feet	Galvanized steel - 60 x 60m - height 55mm - adjustable 30mm
Lateral beams	Galvanized steel - length 960mm - 930mm
Floor panels 1 x 1m x 22mm Panels (Woods and colours by request)	

X'PO FLOOR

Description

X'po floor is a new structural system designed to create flooring for all types of expositions.

- Developed to respond to several constraints:
- Use metric modules
- Allow the passage of wiring and pipes
- Bear heavy loads up to 1,500 kg/m²
- Create split levels
- Allow indirect lighting
- Offer a range of special coatings

The X'po floor structure is simple and quick to install.

X'po floor's strength: MODULARITY

With three types of parts, supports, lateral beams, and floor panels, display shelves you can give free rein to your imagination and design your booth the way you want it.

The X'po floor advantage: DURABILITY

The floor panels are reusable from exposition to exposition. This system reduces the cost of your expositions and helps protect the environment.

Customize your booth

Space below the floor





System

The multi-position support is the key component of the X'po floor system. It is composed of 16 holes into which the lateral beams fit. It can be placed anywhere it is necessary to form a 1×1 m grid without ever being exposed.





The X'po floor system is based on an assembly of multi-position supports and lateral beams, forming a grid upon which the floor panels rest.











Split raised levels for display shelves







Finishes

The entire edge is finished with a perforated decorative grid that fits into the lateral beam. The perforations in the grid allow a booth to have indirect lighting around the edge.



Decorative granular sheet

X'po floor comes standard with wood finish floor panels that bring a Warm, Inviting feeling to a booth...

You may also adapt one or more coverings to your exposition space such as panelling, grass, linoleum, or tile.

Raised display shelf







Technical specifications

Vehicle display

Multi-position support	Aluminium	160 x 160 x 80 mm
Lateral beam	Galvanized steel	920 x 40 x 40 mm
Decorative grill	Galvanized steel	1000 x 120 mm
Floor panels	Standard: MDF wood finish	1 x 1 m x 22 mm
Total ground - floor height: 142mm		

Cadrexpo+ is an adjustable structure that allows the creation of a floor at a specific height, creating levels or split display shelves.

Cadrexpo+ is composed of a metal 1 x 1m frame, panels, and precisely adjustable feet.

Cadrexpo+ gives form to your imagination

CADRE EXPO +

System











> The feet screw into the frames.



- The panels are drilled in each corner. The holes fit over the head of the screws used to attach the feet, blocking the panel.
 - The frames are screwed to each other.







Frames	Epoxy painted steel hammered black finish 30 x 30mm square tube - 1 x 1m
Panels	1 x 1m - 22mm thickness
Height	As needed + 2cm adjustment





atento

Description

A.tent.o is a brand name tent system that defines new standards for guality.



System

Foldable tents can be set up and taken down rapidly. They are compact for storage, and provide unparalleled comfort.

2 persons > 2 minutes







Dark brown Light gray

Ask for our special tent catalogue:

Gray

Black

Create your a.tent.o tent system by selecting from among the various models, sizes, colours, and a wide range of accessories. (Special dimensions and colours by request)



Technical specifications

a.tent.o

Model A	2,30 x 2,30 x 2,02 m* (3,19 m)
Model B	3,00 x 3,00 x 2,02 m* (3,28 m)
Model C	4,50 x 3,00 x 2,02 m* (3,28 m)
Model D	6,00 x 3,00 x 2,02 m* (3,28 m)
Hexagonal tent	Dimensions 3.00 / 4.00 / 6.00m
	Clearance height: 2.02m* (3.48m)

a.tent.o MAXIMAL

4 x 4 m	4,00 x 4,00 x 2,19 m* (4,25 m)
6 x 3 m	6,00 x 3,00 x 2,02 m* (3,28 m)
5 x 5 m	5,00 x 5,00 x 2,15 m* (4,48 m)
8 x 4 m	8,00 x 4,00 x 2,19 m* (4,25 m)

* Clearance height, overall height in parentheses.





Accessories

- Storage crate aluminium option.
- Storage cover for the tent included.













Tents / Refreshment stands / Tables

PROMOSTAND

Description

We have refined these ready-to-use kits that are simple and quick to set up.

Promostands can be used as refreshment stands, promotional stands for winegrowers, for direct sales...

At a height of 1.10m the tables are ideal for direct contact and more relevant product presentation.

The materials are professional quality and not bulky when folded up.

The kits we offer are upgradeable and versatile.





The range of booths ready for sale:

Promo Stand 9



Promo Stand 18

- 1 3 x 3m rapid set-up tent
 - 1 3m wall
 - 3 tables 2 x 0.60m with a height of 1.10m
 - 1 display table skirt

Promo Stand 13



Promo Stand 24



3 tables 2 x 0.60m with a height of 1.10m
1 display table skirt

1 4.50 x 3 m rapid

set-up tent

1 4.50m wall

- 1 6 x 3m rapid
- set-up tent
- 1 6m wall
- 3 tables 2 x 0.60m
- with a height of
- 1.10m
- 1 display table skirt Several possible upgrades are available

- 1 6 x 4m rapid set-up MAXIMAL tent

- 1 6m wall 3 tables
- 2 v 0 40~
- 2 x 0.60m with a height of 1.10m - 1 display table
 - skirt

Accessories

Pub tables





Accessories for folding tents



Tents / Refreshment stands / Tables

► High tables



25















QUATTRO



System

The Quattro booth is composed of:

Framing: Galvanized steel tubing *Setup:* Tongue and groove assembly Blocking with wing nuts

Blocking with wing nuts *Covering:* Composed of a roof tarp with valances (that drop from the roof) and a surround (skirting between the counter and the ground) closing the stand on 4 sides.

Counter: 4 white expanded PVC shelves 19mm thick.

Shelves are completely waterproof and one is shorter allowing access (50cm opening). *Packing:* In 5 PVC tarp bags with carrying handles and sliding fasteners.

Branding: Reproduction of all brands using a pallet of branding techniques:

- Hot sealed advertising (Publicité soudée proprietary process)
- Ink jet printing
- Screen printing
- Special tarp adhesive

(on the surround and/or valances and/or rear panel) *Weight:* Approximately 180kg

Options:

- Closure curtain (between the roof and the counter).
- Printing directly on the PVC shelves of the counter.
- Pairing kit (allows 2 stands to be connected).























The Maestro booth is a hexagonal (6 sides of 2m) food stand with a counter The area is 10m² with a covered area of 19m² (including roof overhang). The booth's dressing is made of PVC fabric, waterproof and rot-proof. Easy to set up and take down without tools. Storage in carrying bags.







System

The Maestro booth is composed of:

Framing: Galvanized steel tubing *Setup:* Tongue and groove assembly Blocking with wing nuts







Covering: Composed of a roof tarp with valances (that drop from the roof) and a surround (skirting between the counter and the ground) closing the stand on 6 sides.

Counter: 6 white expanded PVC shelves 19mm thick.

Shelves are completely waterproof and one is shorter allowing access (50cm opening). *Packing:* In 5 PVC tarp bags with carrying handles and sliding fasteners.

Branding: Reproduction of all brands using a pallet of branding techniques:

- Hot sealed advertising (Publicité soudée proprietary process)
- Ink jet printing
- Screen printing
- Special tarp adhesive

(on the surround and/or valances and/or rear panel) Weight: Approximately 165kg

Options:

- Closure curtain (between the roof and the counter).
- Printing directly on the PVC shelves of the counter.
- Pairing kit (allows 2 stands to be connected).









The **Solo booth** is a rectangular $(3 \times 2m)$ food stand with a counter. The area is $6m^2$ with a covered area of $7.40m^2$ (including roof overhang). The booth's dressing is made of PVC fabric, waterproof and rot-proof. Easy to set up and take down without tools. Storage in carrying bags.







SOLO



System

El stand Solo se compone de:

Framing: Galvanized steel tubing *Setup:* Tongue and groove assembly Blocking with wing nuts



Counter: 3 white expanded PVC shelves 19mm thick.

Shelves are completely waterproof.

Access through the PVC fabric panel at the rear.

Covering: In 3 PVC tarp bags with carrying handles and sliding fasteners.

Branding: Reproduction of all brands using a pallet of branding techniques:

- Hot sealed advertising (Publicité soudée proprietary process)
- Ink jet printing
- Screen printing
- Special tarp adhesive

(on the surround and/or valances and/or rear panel) *Weight:* Approximately 90kg

Options:

- Closure curtain (between the roof and the counter).
- Printing directly on the PVC shelves of the counter.













28 Tents / Refreshment stands / Tables



Our Spacio reception tents are the perfect ally for your outdoor receptions and events, removing concern for rain or sun that is too bright.

A modular structure of 5 meter bays: $5 \times 4m$, $5 \times 8m$, $5 \times 12m$ offering you an easy to use space of $20m^2$, $40m^2$, or $60m^2$. Durable material, easy to set up (tongue and groove) to welcome people at cultural or sports events, company parties...

Very stable on the ground, even on windy days. Simplified set-up: all angles are equal Longest structural component: 3.65m. Anti-pocketing trusses in the roof structure. Lateral diagonal beams to reinforce overall stability.







System

The Spacio tents are composed of:

Framing: 40mm Galvanized steel tubing, 2mm thickness.

Setup: Approximately 45 minutes, ideally by 4 people. Assembles by overlapping joints (waisted tubes). Surface bars are detachable (standard). Guying is completed with straps (1 per post).

Covering: Composed of a roof tarp + 2 gabled 5m curtains + 4m side curtains. PVC tarps 650 g/m², M2 fire retardant. Attachment to the framing is simple and quick (elastic cord; straps).

Branding: Reproduction of all brands using a pallet of branding techniques (hot sealed advertising, digital printing) on the valances (that drop from the roof), curtains, and roof.

(on the surround and/or valances and/or rear panel)

Weight: • 95kg for the 5 x 4m tent • 190kg for the 5 x 8m tent

• 280kg for the 5 x 12m tent.

Technical specifications

Covered area	Depending upon the selected structure - from 20 to $60m^2$
Height	Grit (at the sides) = 2.10m; Ridge = 3.50m
Structure	Frame of 40mm diameter galvanized steel tubing, 2mm thickness
Options	- Adjustable height feet. - Wall curtains of striped material. - Clear windows. - Doors. - Junction gutter between 2 tents.









Folding

The **Rapido booth** is a hexagonal food stand with a counter. The floor area is $10m^2$.

The booth's dressing is made of PVC fabric, waterproof and rot-proof. Height adjustable 100% aluminium structure.











System

The Rapido booth is composed of:

Framing: 100% aluminium structure with polypropylene joints and reinforced oval glazing bars. Unfolds rapidly without tools or screws.

Blocking with button fasteners.

Covering: Composed of a roof tarp with valances (that drop from the roof) and a surround (skirting between the counter and the ground) closing the stand on 6 sides.

Counter: 6 varnished solid pine shelves with adjustable aluminium feet.

Packing: In 3 PVC tarp bags with carrying handles and sliding fasteners.

Branding: Reproduction of all brands using a pallet of branding techniques:

- Hot sealed advertising (Publicité soudée - proprietary process)

- Ink jet printing
- Screen printing
- Special tarp adhesive

(on the surround and/or valances and/or rear panel) *Weight*: Approximately 60kg

Options:

- Closure curtain (between the roof and the counter).
- 30kg ballast to maintain stability on the ground.



30 Tents / Refreshment stands / Tables

TABLES AND BENCHES

Description

Our Tables and benches are perfect for your receptions and events.

Practical and durable for any location. Uncompromising quality control. Table of 25mm solid pine. Top of the line wood: Spruce "free of heart centre". UV Resistant varnish - very high quality adhesive. Feet lock easily. Folding supports with safety catches. Casters to protect flooring. Wood lateral beams under the platform to facilitate stacking and storage. Very stable in use. "ISO 9001" reinforced supports.



Usage

Our Tables and benches are foldable and usable indoors and outdoors. They are suitable for your cultural and sports events, bazaars, fairs...









Technical specifications

Folding tables and benches	Length (in cm)	Width (in cm)	Thickness (in cm)
	220	50	2,5
Standard table	200 ou 220	60	2,5
	200 ou 220	67	2,5
	200 ou 220	80	2,5
Standard bench	200 ou 220	27	2,8
Bench with backrest	220	27	2,8





XPANDIT

Description

There are many to Xpandit fences:

- Manufactured of polypropylene and PVC
- Heat resistant
- Easy to store, handle and transport
- Requires no maintenance
- Light
- Durable material
- Does not rust
- Does not conduct electricity
- Will not mark floors
- Can be used indoors and outdoors
- Simple, easy assembly
- Quick and effective barrier to access
- Immediate delivery
- Optional wheels to simplify handling



Usage locations

- Shows and expositions
- Convention centres
- Hotels and receptions
- Shopping centres
- Parking areas
- Stations, Airports, Ports
- Schools and universities
- Hospitals
- Sports centres
- Roadways and construction sites
- Movie houses and theatres









Technical specifications

Width (open)	3,5 m
Width (closed)	0,42 m
Height	1 m
Weight	7 Kg



Fences / Speeds bumps

XpanDit —

TRANSIT SPEED BUMPS

Transit —

Description

Transit speed bumps are easy to install. Visible from a distance, it is colourfast and reflective. The bottom side has a non-skid strip. Transit speed bumps require no maintenance and it is very easy to transport.



Usage for police controls, work on public roadways, school entrances and exits, parties and events...



Transit portable speed bump

MINIT



Technical specifications

Length	3 m
Width	22 cm
Height	4 cm
Weight	13 Kg

Description

The Minit fence is elegant, light, and easy to handle.

Its advantages:

- Light
- Does not rust
- Customizable
- Comes in several colours
- Stacks easily
- Will not damage flooring
- For indoor and outdoor use
- Compatible with Movit and Xtendit



Technical specifications

Length	1,25 m
Height	1 m
Weight	7 Kg







м і <u>N</u> і ť —





Fences / Speeds bumps

XTENDIT

xtenpit —

Description

Xtendit fences are components manufactured of polypropylene with a length of 1.55m. Available in the same colours as the MOVIT and MINIT fences.

Usage together with MOVIT and MINIT fences can help reduce the cost per linear meter of enclosure.

Usage

The Xtendit fence is perfectly suited for all uses

- Theme parks
- Sports events
- Shopping centres
- Roadwork
- Restaurants
- Parking areas
- Schools
- Stations
- Hotels

Its advantages

- Economical
- Lightweight
- Does not rust
- Comes in several colours
- Easy to handle and store
- Will not damage flooring
- For indoor or outdoor use
- Compatible with Movit and Xtendit

Economical solution: 2 Xtendit = 1 Movit



Available in these colours:

Yellow - Red - Blue - Green - White - Orange - Gray





Technical specifications

Length	1.55m
Height	26.5cm
Weight	3.5Kg
Maximum load	400Kg
Heat resistance	- 20°C to 55°C
Colours	Paint colour (N.C.)



Fences / Speeds Bumps

Description

Movit fences are environmentally friendly, easy to move, strong, secure fences. It is perfect for all urban usage (events, work, parking areas, schools, stations, hotels, parks, pools...). The characteristics, design and functionality of the Movit fence are highly sought after by private and public users in a wide range of activities.

Customizable with your name and colour... (contact us)





Functional: Quick and easy connection, adjustable levelling.
 Environmentally friendly: manufactured of polypropylene, no rust, installation is not noisy, recyclable.
 Secure: Will not rust, provides greater security for pedestrians and vehicles.



Available in these colours:





Option:



мovit—





Yellow - Red - Blue - Green - White - Orange - Gray



Length	2m
Height	1cm
Weight	12Kg
Maximum load	400Kg
Heat resistance	- 20°C to +55°C
Colours	Paint colour (N.C.)



Rubber feet

Movit fences have been subjected to many quality controls: compression, deformation and strength carried out by the LGAI laboratory, a Catalan government body.

File number: 99011028









A2S INTERNATIONAL 1 rue des Lys F-67520 MARLENHEIM

Tel: +33 (0)3 888 777 88 Fax: +33 (0)3 888 777 78

www.a2s.fr info@a2s.fr

